

Technical Data Sheet

Kunshan EMF Industrial Co., Ltd.	+86 512 571 131 82 Tel
91 Xinpu Road, Kunshan City	+86 512 571 131 83 Fax
P.R.China. 215337	+86 138 626 007 66 Mobile
www.emfcn.com	sales@emfcn.com e-Mail

ENCAPSULATED LIFELINE FOR LIFEBOUY

REFERENCE STANDARD

RESOLUTION MSC.48 (66)

Buoyant lifelines required by regulation 111/7.12 shall:

1. be non-kinking,
2. have a diameter of not less than 8 mm. and
3. have a breaking strength of not less than 5 kN.

PARTICULARS

Description of Goods: Encapsulated Floating Lifeline for Lifebuoys

Model: HLW830-E

Rope Material: UV resistant Polypropylene fiber (PP), so floating on water

Rope Type: Braided, so Non-Kinking (or 8 strands).

Rope Color: Safety Orange

Rope Size: Diam. 8 mm x 30 Mtrs.

Cover Material: UV resistant HDPE with rubber plug.

Suitable for: EMF Marine Lifebuoys XT5555 and XT5555-1, or other lifebuoys with inner diameter 440mm to 450mm.



Important: This datasheet is subjected to change without notice.